

3144 Colorimetric Hydrazine Analyzer

Precise and accurate Hydrazine monitoring with Waltron's easy-to-maintain colorimetric analyzer

Waltron's 3144 Hydrazine Analyzer is the first choice for online colorimetric analysis of hydrazine in ultrapure water applications. The 3144 is trusted worldwide to deliver accurate and reliable readings with easy maintenance and a low total cost of ownership. Common application points in a boiler system for online hydrazine measurement include the deaerator, condensate system, and boiler feedwater.



Key Features

- Accurate and wide-range analysis (PPB & PPM)
- 100% tooless wet section
- Pre-assembled pump/sample heads for quick changeout
- Automatic calibration and validation (QA/QC)
- Color touchscreen display

- Grab sample capability
- Internal datalogger with easy USB port on door
- Standard motion sensor LED light and color active alarm indicators
- Automatic start/stop based on sample flow detection with internal loop flow reservoir
- Optional 24-48 hour real time graph



Main: +1 908-534-5100 Fax: +1 908-534-5546 info@waltron.net



3144 Specifications

Specifications

Parameter: Hydrazine

Technology: Colorimetric

Range(s): 0-100ppb, 0-500ppb

Accuracy: (+/-) 2% of reading

Sample Streams: 1 to 2

Response Time: ~12 minutes, batch process

Cycle Time: One reading every 20 mins,

adjustable

Analog Outputs: 4-20mA (galvanic isolator

option) or 0-5V

Alarms: 2 or 4 configurable alarms

(result, loss of sample, fault)

Calibration Method: Automatic

Calibration Frequency: One reading

every 20 mins, adjustable

Ambient Conditions: 10-45°C analyzer (50-113°F)

Sample Temperature: 5-55°C (41-131°F)

Sample Flow/Pressure: 100-500 ml/min;

atmospheric

Mechanical

Power: 110-220VAC

IP Rating: IP65/NEMA4X

Dimensions: 24x15x8.5 (60x38x21cm)

Weight: 38lbs / 17kg

Mounting: Panel/Wall

Materials: Corrosion-resistant Stainless Steel

Sample Connection: 1/4 (0.635cm) OD Swagelok

Maintenance Cycle: Monthly reagents,

quarterly tubing





