

3152 Disinfectants Analyzer

Precise Disinfectants Monitoring with
Waltron's Easy-to-Maintain Analyzer

Waltron's 3152 Disinfectants Analyzer is the first choice for online analysis of monochloramine. The 3152 is trusted worldwide to deliver accurate and reliable readings with easy maintenance and a low total cost of ownership. Typical applications are potable water, cooling water, industrial wastewater, and swimming pools.



Key Features

- Accurate and wide-range analysis
- 100% toolless wet section
- Pre-assembled pump/sample heads for quick changeout
- Automatic calibration and validation (QA/QC)
- Color touchscreen display
- Grab sample capability
- Internal datalogger with easy USB port on door
- Standard motion sensor LED light and color activealarm indicators
- Automatic start/stop based on sample flow detection with internal loop low reservoir
- Optional 24-48 hour real time graph



Get in Touch

Waltron Group Headquarters
25 Minneakoning Road, Suite 101
Flemington, NJ 08822 USA

Main: +1 908-534-5100
Fax: +1 908-534-5546
info@waltron.net

Specifications

Parameter: Disinfectants

Technology: Colorimetric

Range(s): 0-5ppm

Accuracy: (+/-) 5% of the measuring reading

Sample Streams: 1 to 2

Response Time: ~12 minutes, batch process

Cycle Time: One reading every 20 mins, adjustable

Analog Outputs: 4-20mA (galvanic isolator option) or 0-5V

Alarms: 2 or 4 configurable alarms (result, loss of sample, fault)

Calibration Method: Automatic

Calibration Frequency: One reading every 20 mins, adjustable

Ambient Conditions: 10-45°C analyzer (50-113°F)

Sample Temperature: 5-55°C (41-131°F)

Sample Flow/Pressure: 100-500 ml/min; atmospheric

Mechanical

Power: 110-220VAC

IP Rating: IP65/NEMA4X

Dimensions: 24x15x8.5 (60x38x21cm)

Weight: 38lbs / 17kg

Mounting: Panel/Wall

Materials: Corrosion-resistant Stainless Steel

Sample Connection: 1/4 (0.635cm) OD Swagelok

Maintenance Cycle: Monthly reagents, quarterly tubing

