

# 4095 Multi-Conductivity Analyzer

Advanced Multi-Conductivity and pH Monitoring with Waltron's 4095 Analyzer

The Waltron 4095 Multi-Conductivity Analyzer delivers innovative technology for precise water and steam monitoring, tailored for power plants and industrial facilities. It offers unparalleled accuracy, streamlined single-transmitter displays, and easy data logging. Supported by Waltron's service team, the 4095 ensures reliable and efficient conductivity and pH analysis.



## Key Features

- Conductivity measurement range: 0.055 to 1000 uS/cm
- Calculation of pH value in the range from pH 7.5 to 11.5
- Space-saving panel mount
- Calculation of alkalizing reagent consumption, e.g. ammonia in the range from 0.01 to 10 ppm.
- Simultaneous measurement and display of specific and cation conductivity, pH, alkalizing reagent, sample temperature and sample flow
- Temperature compensation preset for strong acids (wide range selectable for other sample conditions)
- Optional 4010 resin cartridge assembly
- Extremely low power consumption
- 1/4-DIN cutout with color touchscreen
- Connects to a wide variety of specific conductivity sensors



Get in Touch

Waltron Group Headquarters  
25 Minneakoning Road, Suite 101  
Flemington, NJ 08822 USA

Main: +1 908-534-5100  
Fax: +1 908-534-5546  
info@waltron.net

## Specifications

---

**Parameter:** Specific/Cation/Calculated pH

**Technology:** Contacting

**Range(s):** 0-9.999  $\mu\text{S}/\text{cm}$ , 0-99.99  $\mu\text{S}/\text{cm}$

**Accuracy:** (+/-) 1% of measured value or  
+/- 1 digit (whichever is greater)

**Sample Streams:** 31-Dec

**Response Time:**  $t_{90}$ : < 5 seconds

**Cycle Time:** Continuous

**Analog Outputs:** 4 x 0/4 - 20 mA  
for measured signals

**Digital Outputs:** Optional RS422/RS485

**Alarms:** General Alarm

**Calibration Method:** Process

**Calibration Frequency:** Probe-dependant

**Ambient Conditions:** 0-130°F / -20-55°C

**Sample Temperature:** Probe-dependant

**Sample Flow/Pressure:** Probe-dependant

## Mechanical

---

**Power:** 110 to 240 VAC, 48 to 63 Hz

**IP Rating:** IP 66, NEMA 4X

**Mounting:** Panel

**Materials:** High Strength ABS

