Waltron

EXPERTS IN WATER CHEMISTRY SINCE 1903

3048 DISSOLVED IRON ANALYZER

The Waltron 3048 Dissolved Iron Analyzer provides you with cutting-edge technology for online measurement of dissolved iron in ultrapure water applications.

Online dissolved iron analysis is a growing in popularity as an effective method to monitor corrosion within steam and boiler water systems. Upgrade your manual bench test process to automatic online analysis for accurate and reliable results, greatly enhanced visibility on changes in iron concentrations, and earlier detection of potential problems.



FEATURES

Accurate and wide-range analysis

Multi-stream available

Fast loop reservoir

Adjustable cycle and calibration frequency

Automatic calibration and validation (QA/QC)

Compact design

Color touchscreen display

Grab sample capability

Internal datalogger

Low reagent level alarm

Automatic start/stop based on sample flow detection

Minimal analyzer maintenance

Wet Section





See reverse side for specifications.

3048 DISSOLVED IRON ANALYZER | GENERAL SPECIFICATIONS

PERFORMANCE

Range	0-250 ppb, 0-500ppb, 0-5 ppm (internal dilution)
Accuracy	+/- 2% of full scale
Reproducibility	+/- 2% of reading
Analysis Time	8 min, batch process
Sampling Frequency (Cycle Time)	One reading every 20 minutes (adjustable)
Required Maintenance	Once a month replenish reagents, Quarterly replace tubing
Reagent Consumption (approx.)	1 reagent, 1L per month
Sensor Classification	Colorimetric with glass flowcell and LED source
Application	Boiler water and cooling water
Ambient Temperature Range	10-45°C analyzer (50-113°F)
Atmospheric Pressure Range	No Limits
Humidity	Up to 90% not condensable
Unit Dimensions	Height=23.6"(60 cm), Width=15"(38 cm), Depth=8.3"(21 cm)
Positioning and Installation Details	Wall mounting, bench supported, panel mounting (optional)
Weight	17 kg (37.5 lbs.)
Degree of Protection	IP55 (NEMA 4): Wet section, IP65 (NEMA 4x): Electronics
Alarms	2 or 4 configurable alarm relays (Result, loss of sample, fault)
Power Supply	110-220Vac, 50-60 Hz 80 VA
CE Certification (on request)	Meets low voltage and low electromagnetic compatibility directives
SAMPLE DELIVERY OPERATING CONDITIONS	
Temperature Range	5-55°C (41-131°F)
Inlet Sample	100-500 ml/min, atmospheric, flexible tubing O.D. 1/4"(6 mm)
Outlet Sample	Atmospheric, waste tubing O.D. 3/8"(9 mm)
PH	3-12
Sample Conditioning Requirements	Filtering between 10 and 60 micron, depending on the matrix, needed only to avoid clogging
Materials in Contact with Sample	Glass, Silicone, Plexiglass, Stainless Steel AISI 316
SIGNAL OUTPUTS	
Analog Outputs	4-20mA (galvanic isolator module available as option) or 0-5V
Serial I/O Options	RS232; RS485; MODBUS; PROFIBUS
OPERATIONAL CALIBRATION	
Single/Multi-Point	Multi-Point: zero and mid-range
Matrix Corrections	Yes, sample blank correction
Manual/Automatic	Both



WALTRON GROUP HEADQUARTERS 25 Minneakoning Road, Suite 101 Flemington, NJ 08822 USA Phone: +1 908 534 5100 Fax: +1 908 534 5546 www.waltron.net 102-032-B.1