

EXPERTS IN WATER CHEMISTRY SINCE 1903

3142 Phosphate Analyzer

Accurate Phosphate Monitoring with Waltron's Easy-to-Maintain Analyzer

Waltron's 3142 Phosphate Analyzer is the first choice for online analysis of dissolved phosphate in ultrapure water applications. The 3142 is trusted worldwide to deliver accurate and reliable readings with easy maintenance and a low total cost of ownership. Common application points in a boiler system include make-up water, condensate, boiler feedwater, saturated steam/main steam, and cooling water.



Key Features

- Accurate and wide-range analysis (PPB & PPM)
- 100% tooless wet section
- Pre-assembled pump/sample heads for quick changeout
- Automatic calibration and validation (QA/QC)
- Color touchscreen display

- Grab sample capability
- Internal datalogger with easy USB port on door
- Standard motion sensor LED light and color active alarm indicators
- Automatic start/stop based on sample flow detection with internal loop flow reservoir
- Optional 24-48 hour real time graph



Waltron Group Headquarters 25 Minneakoning Road, Suite 101 Flemington, NJ 08822 USA Main: +1 908-534-5100 Fax: +1 908-534-5546 info@waltron.net



EXPERTS IN WATER CHEMISTRY SINCE 1903

3142 Specifications

Specifications

Parameter: Phosphate

Technology: Colorimetric

Range(s): 0-5ppm, 0-20ppm, 0-150ppm, 0-300ppm

Accuracy: +/- 2% of ful scale

Sample Streams: 1 to 2

Response Time: ~9 minutes, batch process

Cycle Time: Every 15 mins

Analog Outputs: 4-20mA (galvanic isolator option) or 0-5V

Alarms: 2 or 4 configurable alarms (result, loss of sample, fault)

Calibration Method: Manual or Automatic

Calibration Frequency: Every 15 mins

Ambient Conditions: 0-55°C (32-131°F)

Sample Temperature: 5-55°C (40-130°F)

Sample Flow/Pressure: 100–500 ml/min; atmospheric

Mechanical

Power: 90-265VAC

IP Rating: IP65/NEMA4X

Dimensions: 66.04cm x 38.1cm x 30.48cm (26" x 15" x 12")

Weight: 17kg (38lbs)

Mounting: Wall Mount Only

Materials: Corrosion-resistant Stainless Steel

Sample Connection: 0.635cm (1/4") OD Swagelok

Maintenance Cycle: Monthly reagents, quarterly tubing



W Waltron



VISIT THIS PRODUCT PAGE ON WALTRON.NET Main: +1 908-534-5100 Fax: +1 908-534-5546 info@waltron.net