

3154 Filming Amines Analyzer

Accurate Filming Amines Monitoring with Waltron's Easy-to-Maintain Analyzer

The Waltron 3154 Filming Amines Analyzer is the first analyzer designed for online analysis of film-forming amine products in clean water. It delivers accurate, reliable readings with low maintenance and cost. Its touchscreen interface simplifies operation, while the fast-loop reservoir ensures precise, independent measurements. Ideal for boiler cycle and process water applications, it uses proprietary reagent technology.



Key Features

- Accurate and wide-range analysis (PPB & PPM)
- 100% tooless wet section
- Pre-assembled pump/sample heads for quick changeout
- Automatic calibration and validation (QA/QC)
- Color touchscreen display

- Grab sample capability
- Internal datalogger with easy USB port on door
- Standard motion sensor LED light and color active alarm indicators
- Automatic start/stop based on sample flow detection with internal loop low reservoir





3154 Specifications

Specifications

Parameter: Filming Amines

Technology: Colorimetric

Range(s): 0-500ppb

Accuracy: +/- 10 PPB or +/- 5% of reading, whichever is greater {Drop Stream 1 or 2}

Sample Streams: 1 to 2

Cycle Time: ~12 minutes, batch process

Calibration Frequency: One reading every

20 mins, adjustable

Analog Outputs: 4-20mA (galvanic isolator

option) or 0-5V

Alarms: 2 or 4 configurable alarms

(result, loss of sample, fault)

Calibration Method: Manual or Automatic

Ambient Conditions: 0-55°C (32-131°F)

Sample Temperature: 5-55°C (41-131°F)

Sample Flow/Pressure: 100-500 ml/min;

atmospheric

Mechanical

Power: 90-265VAC

IP Rating: IP65/NEMA4X

Dimensions: 66.04cm x 38.1cm x 30.48cm

(26" x 15" x 12")

Weight: 17kg (38 lbs)

Mounting: Wall Mount Only

Materials: Corrosion-resistant Stainless Steel

Sample Connection: 0.635cm (1/4") OD

Swagelok

Maintenance Cycle: Monthly reagents,

quarterly tubing





